



00419-860 Boilersuit with kneepad pockets

MASCOT® SAFE CLASSIC

14

82C42	82C44	82C46	82C48	82C50	82C52	82C54
82C56	82C58	82C60	82C62	82C64	82C66	82C68
82C70	82C72	90C42	90C44	90C46	90C48	90C50
90C52	90C54	90C56	90C58	90C60	90C62	90C64
90C66	90C68	90C70	90C72			



- The surface treatment makes the product dirt-repellent and ensures high visibility.
- Durable triple stitched seams that extend the product life.
- Access to trousers underneath from both sides.
- Elastic and pleat in the back.
- Adjustable kneepad pockets so kneepads can be optimally placed on the knee.

Technical info

Fluorescent with reflective tape. The surface treatment makes the product dirt-repellent. Triple stitched seams on sleeves, leg and crotch. Fastening with two-way zip, storm flap and press studs. Chest pocket with flap and press stud. Phone chest pocket with adjustable flap and pen pocket. Front pockets. Inner pocket with zip. Access to trousers from both sides. Back pockets with reinforcement, flap and hook and loop band fastening. Adjustable hammer loop. Thigh pocket with flap and hook and loop band fastening. Ruler pocket. Adjustable kneepad pockets. Sleeve pocket with hook and loop band fastening. Cuffs with press stud fastening. Elastic and pleat in the back. Ventilation under sleeves. Co-certified together with kneepad type large in accordance with EN 14404-3.

User



Main material/upper material

65% polyester/35% cotton

290 g/m²



Twill. Do not soak. Wash separately. The product is certified to retain its properties with 50 domestic washes or 50 industrial washes. The dirt-repellent finish is reactivated by tumble drying according to the washing instructions.

Industrial care category B1

Certifications



- OEKO-TEX® STANDARD 100
- EN ISO 20471 - class 3
- Hi-Vis Group A
- GO/RT 3279, ONLY colour 14
- RIS-3279-TOM, ONLY colour 14

Logo

The product is certified with a maximum logo area of 0,9300m². This approved area must not be exceeded. Logos respectively on the front or back of the product, can only constitute a maximum of 50% of the total approved logo area in order to maintain the EN ISO 20471-certification. Note: The listed area is only a guide to how much space is available for logo placement. In order to maintain the product's hi-vis class according to EN ISO 20471, the instructions on logo size must be observed.

Logo placement:

- Workwear logo. Over left breast pocket. Max 10x4 cm/3.9x1.5 inches
- Workwear logo. Left breast pocket. Max 8x5 cm/3.1x1.9

inches

- Workwear logo. Over right breast pocket. Max 10x4 cm/3.9x1.5 inches
- Workwear logo. Mid-back. Max 28x12 cm/11x4.7 inches
- Workwear logo. Left back pocket. Max 10x5 cm/3.9x1.9 inches
- Workwear logo. Right back pocket. Max 10x5 cm/3.9x1.9 inches
- Workwear logo. Vertical on left thigh, read from the bottom upwards. Max 15x5 cm/5.9x1.9 inches
- Workwear logo. Horizontal on left thigh. Max 11x5 cm/4.3x1.9 inches
- Workwear logo. Vertical on right thigh, read from the top downwards. Max 15x5 cm/5.9x1.9 inches
- Workwear logo. Horizontal on right thigh. Max 11x5 cm/4.3x1.9 inches
- Workwear logo. Special placement. Contact to discuss further