



- Breathable, wind and waterproof with taped seams.
- Unique CLIMASCOT® insulation provides warmth without bulk. Lightweight, soft CLIMASCOT® insulation takes up almost no space when compressed.
- Phone pocket under storm flap with zip and a small opening to a headset cord.
- Durable CORDURA® - reinforcement at the wrist to extend product life.
- Extra protection against the cold with an extended back.
- The hood fits over a helmet.

Technical info

Fluorescent, with vertical and oblique transverse reflective strips. Breathable, wind and waterproof. Taped seams. CLIMASCOT® Lightweight Insulation. Padded. Quilt lining in sleeves. High collar. Ribbed inner collar. Detachable lined hood can be adjusted to fit over a helmet via drawstring. Adjustable wire on both sides of the hood. Fastening with zip and storm flap with press studs. Zipped inner pockets under storm flap - one designed especially for a mobile with holes for headset wire and guide loops to keep wire accessible. Zipped pocket under storm flap large enough to hold a 9.4-inch tablet. Chest pocket with a zip. Chest pocket with flap and press stud. D-ring. Ergonomically shaped sleeves allow for great freedom of movement. Front pockets with a zip. Internal drawstring adjustment at the hip. Zip at lower back for logo printing/ embroidery. Extended back. Waterproof pen pocket. Rib (hidden in storm flap) at cuffs. CORDURA® fabric reinforced cuffs with press stud fastening.

User



20535-231 Winter Jacket

breathable - wind- and waterproof - padded
 MASCOT® SAFE SUPREME



S	M	L	XL	2XL	3XL	4XL
---	---	---	----	-----	-----	-----

Main material/upper material

100% polyester
 210 g/m²



Ripstop. Hydrostatic pressure test > 10,000 mmH₂O according to EN ISO 811. According to EN ISO 20471, this product is certified to retain its properties with 50 domestic washes.

Industrial care category B3

CORDEXA CLIMASCOT®
 F A B R I C Lightweight Insulation

Certifications



- OEKO-TEX® STANDARD 100
- EN ISO 20471 - class 3
- Hi-Vis Group A
- EN 342 3/WP (2.2516 clo)
- EN 343 4-1-X
- RIS-3279-TOM, ONLY colour 14

Logo

The product is certified with a maximum logo area of 0,2400m². This approved area must not be exceeded. Logos respectively on the front or back of the product, can only constitute a maximum of 50% of the total approved logo area in order to maintain the EN ISO 20471-certification. Note: The listed area is only a guide to how much space is available for logo placement. In order to maintain the product's hi-vis class according to EN ISO 20471, the instructions on logo size must be observed.

Logo placement:

- Workwear logo. Left breast. Max 8x7 cm/3,1x2.7 inches
- Workwear logo. Mid-back. Max 25x20 cm/9.8x7.8 inches
- Workwear logo. Horizontal on right sleeve. Max 10x5 cm/3.9x1.9 inches
- Workwear logo. Special placement. Contact to discuss further





