

21009-284 Jacket

ULTIMATE STRETCH - two-toned - flame retardant
 MASCOT® ACCELERATE MULTISAFE



S	M	L	XL	2XL	3XL	4XL
5XL						



- A high level of protection with anti-static, acid protection and flame retardant properties.
- Protects from electric arcs.
- A high level of wear resistance and the ultimate freedom of movement.
- Fastening with zip and double storm flap.
- The quick release zip allows you to open the zip fastener quickly.
- Strap for gas alarm.
- Suitable for Industrial Laundering.
- Find the corresponding jacket 21008-284, specially designed and tailored for women.

Technical info

Two-toned. Fluorescent, with oblique transverse reflective strips. ULTIMATE STRETCH. Anti-static, acid-protective and flame retardant. Protects from electric arcs. High collar. Quick release zipper closure and double storm flap. Strap for gas alarm. Chest pockets with zip. Prepared for attachment of ID card. Front pockets with a zip. Elastic at cuffs and waist. With print effects.

User



Main material/upper material


40% modacrylic/28% cotton/19% polyamide/7% elastolefin/5% aramid/1% carbon fibres
 290 g/m²



ULTIMATE STRETCH. According to EN ISO 20471, this product is certified to retain its properties with 50 domestic washes or 40 industrial washes. Impregnation is required after each wash to maintain EN 13034 protection.

Industrial care category B1

Certifications



- OEKO-TEX® STANDARD 100
- EN 1149-5 (tested according to EN 1149-3)
- EN ISO 11612 (A1, A2, B1, C1, E1, F1)
- EN 13034 (Type 6)
- EN 13034, category J
- EN 61482-1-2 APC 1 (front & sleeves APC2)
- EN IEC 61482-1-1 (ELIM 7,7 cal/cm², ATPV 9,5 cal/cm², front and sleeves ELIM 31 cal/cm², ATPV 38 cal/cm²)
- EN ISO 20471 - class 2
- Hi-Vis Group A
- ProWash®

Logo

Due to the unique properties of the fabric, logo printing is only available through the use of specific transfer types. As this is a safety product, we strongly recommend that MASCOT affix the logo to reduce the risk of errors. Please contact customer service for further information.

The product is certified with a maximum logo area of 0,4400m². This approved area must not be exceeded. Logos respectively on the front or back of the product, can only constitute a maximum of 50% of the total approved logo area in order to maintain the EN ISO 20471-certification. Note: The

listed area is only a guide to how much space is available for logo placement. In order to maintain the product's hi-vis class according to EN ISO 20471, the instructions on logo size must be observed.

Logo placement:

- Workwear logo. Special placement. Contact to discuss further