



21301-292 Outer Shell Jacket

two-toned - flame retardant - ULTIMATE STRETCH
 MASCOT® ACCELERATE MULTISAFE



S	M	L	XL	2XL	3XL	4XL
5XL						

Main material/upper material

36% modacrylic/25% cotton/18% polyamide/9%
 polyurethane/6% elastolefin/5% aramid/1% carbon fibres
 335 g/m²



- A high level of protection with anti-static, acid protection and flame retardant properties.
- Protects from electric arcs.
- Windproof and waterproof with taped seams.
- Stretch material provides optimal freedom of movement.
- Extra fabric at the lower back protects you from the weather.
- The quick release zip allows you to open the zip fastener quickly.
- Strap for gas alarm.
- To maintain EN ISO 20471, class 3, only hoods (21410, 21510) in colour 17 may be added.

Technical info

Wind and waterproof. Taped seams. Two-toned. Fluorescent, with oblique transverse reflective strips. ULTIMATE STRETCH. Anti-static, acid-protective and flame retardent. Protects from electric arcs. High collar. Quick release zipper closure and double storm flap. Strap for gas alarm. Chest pockets with a zip. Prepared for attachment of ID card. Front pockets with a zip. Extra fabric at the lower back protects you from the weather. With print effects. Supplement the product with a hood, 21410-292 or 21510-292 (see MASCOT® COMPLETE).


User



ULTIMATE STRETCH. Ripstop. Shrinkage max. 3%. According to EN ISO 20471, this product is certified to retain its properties with 25 domestic washes. Impregnation is required after each wash to maintain EN 13034 protection.

Industrial care category B3

Certifications



- OEKO-TEX® STANDARD 100
- EN 1149-5 (tested according to EN 1149-3)
- EN ISO 11612 (A1, B1, C1, E2, F1)
- EN 13034 (Type 6)
- EN 13034, category J
- EN 61482-1-2 APC 2
- EN ISO 24232 4-1-X
- EN IEC 61482-1-1 (ELIM 30 cal/cm², ATPV 34,6 cal/cm²)
- EN ISO 20471 - class 3
- Hi-Vis Group A

Logo

Due to the unique properties of the fabric, logo printing is only available through the use of specific transfer types. As this is a safety product, we strongly recommend that MASCOT affix the logo to reduce the risk of errors. Please contact customer service for further information.

The product is certified with a maximum logo area of 0,1300m². This approved area must not be exceeded. Logos respectively on the front or back of the product, can only constitute a maximum of 50% of the total approved logo area in order to maintain the EN ISO 20471-certification. Note: The listed area is only a guide to how much space is available for

logo placement. In order to maintain the product's hi-vis class according to EN ISO 20471, the instructions on logo size must be observed.